602 Crate Dirt Sportsman Modified rules for PASS event at Stafford Motor Speedway

2012 Dirt Sportsman Modified rules apply with the following addendums.

www.dirtcarmembers.com

- 1. 602 GM Crate Motor; Must be sealed. Total weight w/driver 2400lbs with aluminum wheels 2350lbs with steel wheels. Anyone tampering with seals or modifying motors will be DQd from the event.
- 2. Left side weight-maximum 55% without driver
- 3. Rear weight- Minimum (must have) 58% without driver.
- 4. Brakes- Maximum rotor width .810"
- 5. Shocks-\$160.00 max price limit on shocks. Must be readily available for \$160.00. Steel only.
- 6. No right side steering Must have conventional steering box mounted in drivers compartment and must have one drag link connecting to steering box to steering arm.
- 7. Belly pans must be made of .50 aluminum only.
- 8. Maximum front axle width 52" measured at center of king pin at axle center line.
- 9. Rear offset is measured from center line of rear to inside of tire sidewall. The difference between the two measurements can be no larger than 10" with a ½" maximum tolerance up to 10.5".
- 10. Radiator must be minimum 22" high and vertical.
- 11. No electric fans.
- 12. Bodies must be conventional DIRT style, No sail panels and/or wings.
- 13. No inboard springs on front end. Springs must be mounted outside of frame rails.
- 14. Seat must be centered in car.
- 15. Lead and/or weight of any kind is not to be mounted on door bars or rub rail hoops. 1" diameter door bars only and 1 ½ maximum diameter rub rail and hoops only.
- 16. Wheel offsets; no more than 6" offset or less than 3" on any corner.
- 17. No gear rule. Must use MSD# 87285 rev control box or 6200 rpm chip.
- 18. Fuel cell minimum height 12" from ground and must be centered between frame rails and in line with engine centerline.
- 19. Racing Gasoline only. No oxygenated fuels. No MTBE. No fuel additives. Sunoco Race Fuel decals only. Sunoco Race Fuel will be available at the event.
- 20. Engine tilt-back no more than 3 degrees.
- 21. No rear sway bars.
- 22. Roll cage height minimum 47" front hoop and 52" rear hoop from bottom 2x4.
- 23. All cars must be under 95DBA. Exhaust must be turned down.
- 24. It is required that you have a Raceceiver Radio so that race control can speak to you if necessary. There will be no radios for purchase/rental available at the track. This is a Must.
- 25. It is required that all cars run a Transponder for scoring purposes. Transponders can be ordered directly from AMB. There will be NO transponders available for

- purchase/rental at the event. We will need your transponder number when you enter the event.
- 26. Tires; Hoosier; Dirt spec. RR H75, D500, RF 13x82 spec. Left side D400 or spec. and/or American Racer; RR 29x11x15 D3B, LR 27.5x11x15 D1B. No asphalt and/or Dirt late model tires. Tires must have chain-link type tread pattern. No slicks. No chemical tire softeners. We will have a trained explosive /chemical sniffing dog on-site to check all cars lined up before the feature event, any cars failing this test will be removed from competition.
- 27. Any item not covered in the rules must be approved by the "Commissioner of Racing"; John Holland @ New England Race Fuel. Inc. office # 860-673-9555 or www.johnholland@snet.net

Special Notes:

- 1. The first car across the line that has Hoosier tires on all 4-wheeels will receive a preferred qualifying position for Super Dirt Week. (must attempt to qualify).
- 2. The event winner will receive a guaranteed starting position for the 602 Crate Dirt Sportsman race at Oswego Speedway on Friday August 31. This will start off their Classic weekend.(must attempt to qualify) www.oswegospeedway.com
- 3. Event Purse; \$1,000, 500, 300, 250, 225, 200, 175, 150, 125, 100 thru 24th.